



We fabricate glass for  
the construction industry



## European quality glass fabricated in the United States

PRESS GLASS is a leading architectural glass fabricator with a state-of-the-art production facility in Ridgeway, Virginia, United States and 13-production facilities in Europe. Operations commenced in the USA in 2017, with our current footprint totaling over 270,000 sqft. of production space. We offer a wide range of exterior and interior architectural glass products that meet the tightest aesthetic and performance requirements for your projects.



### ARCHITECTURAL GLASS:

	Glass thickness	Max. Dimensions	Max. Weight
IG Units	up to 4" IGU	126" x 236"	4400 lbs
Laminated	5/32" - 3/4"	126" x 236"	3958 lbs
Tempered	3/16" - 3/4"	126" x 236"	2080 lbs
Heat Strengthened	3/16" - 3/8"	126" x 236"	2080 lbs
Heat Soak Test	3/16" - 3/4"	126" x 236"	2080 lbs
Digital Print <small>up to 1410 DPI</small>	3/16" - 3/4"	126" x 236"	1102 lbs
Spandrel	3/16" - 3/4"	100" x 236" <small>Ceramic Frit</small> 126" x 236" <small>Digital Print</small>	1102 lbs
Polishing/Edging	5/32" - 3/4"	126" x 236"	2010 lbs
BirdShield	3/16" - 1 3/4"	126" x 236"	2090 lbs

The minimum and maximum dimensions may vary depending on the specific glass make up.

### BIRD FRIENDLY GLASS

- PRESS GLASS BirdShield laser pattern
- PRESS GLASS digital print bird pattern
- Guardian Bird1st™ UV
- Guardian Bird1st™ Etch
- Walker AviProtex®
- VITRO BirdSmart™

### ALL GLASS SYSTEMS

- Entrance systems
- Handrail systems
- Structural systems

**MAX. DIMENSIONS:**  
**126" x 236"**  
3200mm x 5994mm



### QUALITY AND CERTIFICATIONS:

#### IGCC ®

Insulating Glass Certification Council

#### SGCC ®

Safety Glazing Certification Council

#### VITRO CERTIFIED ®

Fabricator and Laminator

#### GUARDIAN SELECT®

Elite Fabricator

#### ISO 9001

Quality Management System

#### ISO 14001

Environmental Management System



We make every effort to ensure that the presented publication contains current information as of the date of print. Due to the continuous development of our product, the range may differ from market to market. Product availability should always be confirmed with the Sales Department.